

Pneumatic Butterfly Valve Lined with FEP

Model: ED671FEP

1. Two pieces full port standard lined ball valves offer high stability, rigidity and eliminating potential leak path.
2. Full port design minimizes pressure losses and increases flow capacities thus reducing energy and pumping costs.
3. Full bore design almost no fluid resistance, and good shut-off performance.
4. It features zero leakage, maintenance-free, one-piece stem and ball design, high sealing performance and can be used under full vacuum service.
5. Lower pressure drop and high flow characterized the efficiency of Elite lined ball valves.
6. It can work as on-off or control valve.
7. It can sustain any corrosive medium in addition to the Molten alkali metals and fluorine elements. It is ideal products used in chlor-alkali, industrial in organic chemicals, metal and mining, nitrogen and phosphatic fertilizers, petroleum refining, pharmaceutical etc.
8. Lining material: PFA, FEP, GXPO etc.
9. Operation methods: Manual, worm gear, electric, pneumatic and hydraulic actuator.
10. Elite lined ball valves are available as per the needs of applications in additional sizes and other than standard materials.



Design/Manufacturer Standard	ASME B16.34, HG/T 3704
Face-to-face Dimension	ASME B16.10, GB/T 12221
Flange Standard	ASME B 16.5, GB/T 9119, DIN, JIS
Inspection and Testing	API 598, GB/T 13927

Model NO.: ED671FEP
 Connection Form: Wafer
 Seal Form: Auto Sealed
 Work Pressure: Low Pressure (Pn<1.6mpa)
 Material of Seal Surface: Soft Sealed
 Application: Industrial Usage
 Liner: FEP
 Pressure: 150lb
 Transport Package: Plywood Case

Driving Mode: Manual
 Structure: Centre Sealing
 Valve Stem: Normal
 Working Temperature: Normal Temperature
 (-40°C<T<120°C)
 Valve Body: Casting
 Diameter: Dn50~2000
 Connector: Wafer